

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

09/856888#3
JC18 Rec'd PCT/PTO 2 9 MAY 2001

Intyg Certificate



Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

(71) Sökande *Pacesetter AB, Järfälla SE*
Applicant (s)

(21) Patentansökningsnummer *9804138-7*
Patent application number

(86) Ingivningsdatum *1998-11-30*
Date of filing

Stockholm, 1999-07-19

För Patent- och registreringsverket
For the Patent- and Registration Office

Evvy Morin
Evvy Morin

Avgift
Fee *170:-*

1998 -11- 3 0

Device in connection with pacersField of the invention.

- 5 The present invention relates to a connector for connecting leads to a housing for an implantable pacer according to the preamble of claim 1.

Background of the invention.

10

- A pacer system normally comprises a pulse generator located in a pacer housing, leads and electrodes at the distal end of the leads. The proximal end of the leads is connected to the pacer housing by means of a releasable connector. The connector comprises a female connector part in the pacer housing. The proximal end of the lead normally is designed as a standardized male connector part and the female connector part normally is standardized to such an extent that it will receive this standardized male connector part.
- 15
- 20 The most common way of fixing or locking the male connector part in the female connector part is to use set screws which are oriented in an orthogonal direction in relation to the male connector part and which are accessible from the outside of the pacer housing. The female connector part
- 25 normally is located in a header molded on to the housing.

- Whilst these set screws generally have a good fixing effect, the screws are somewhat difficult to handle, the screws being small. For this reason, attempts have been made to develop fixing means, which more or less automatically lock the male connector part upon insertion thereof.
- 30

- One such device is for instance disclosed in US A 5,252,090. This device includes two elastically resilient metal tongues in a female connector part. The tongues are situated in a common plane and have a common central line, with a respective free end, which are located oppositely to each
- 35

other. The distance between the two free ends is smaller than the diameter of the male connector part. The tongues will be deflected into the direction of insertion when the male connector part is inserted into the female connector part and the tongues thus will engage and lock the sides of the male connector part. If the male connector part is pulled outwardly from the female connector part, the locking effect will increase. The reason is that the friction between the tongues and the male connector part will draw the tongues in closer contact with the male connector part. The two tongues are integrally connected to two wings extending through openings in the header. The wings are angled in relation to the plane of the tongues. Pressure on the wings will move the tongues out of engagement with the male connector part, which then can be removed.

In similarity with the design using set-screws, the locking means in the above design have to be accessed laterally from the outside. For this reason, the locking means are located in the header in order to avoid openings for manipulation in the parts of the housing in which the electronic parts of the pacer are located. Any openings for the connections in the housing or can into the interior of the housing from the header can be permanently sealed.

Another design of a device for locking the terminal pin of a male connector plug is disclosed in US-A-4,784,141. This device is designed for location in one open end of a bore through a header or through the pacer and is accessible from that end. The male plug is to be inserted through the opposite end of the bore. The locking device comprises a hollow cylindrical part with interior threads and an interior, end flange with a conical interior surface. The locking device further comprises a plug with a central bore and with external threads fitting the interior threads in the cylindrical part. The inner open end of the plug is also provided with a conical surface. A resilient locking ring

with conically shaped sides is located between the respective conical surface on the plug and on the cylindrical part. When the plug is screwed inwardly into the cylindrical part, the conical surfaces on plug and
5 cylindrical part will compress the locking ring inwardly against a connector pin inserted into the locking part. In this way the pin is locked in the locking device.

The primary object of the invention is to provide a
10 connector locking part of the kind described above, which can be used with standard male connector parts, which involves a positive locking effect and which does not need any lateral openings in the connector housing or the pacemaker housing. At the same time, it should be possible
15 to easily remove the male connector part without any need of manual operations involving special tools. The object further is to provide a connector that is suitable for use in so called black holes. Black holes are connectors made directly in the pacer housing without any need for the
20 commonly used molded-on connector parts in the form of headers. A further object is to provide a connector that will indicate visually when the male connector plug has been inserted correctly.

25 Short description of the inventive concept

The primary object is achieved in that a connector according to the preamble of the appended claim 1 is provided with the features set forth in the characterizing part of claim 1.
30

Preferred embodiments are set forth in the dependent claims.

Short description of the appended drawings.

35 Figs 1 - 1a illustrate the component parts of a locking device for a female connector part in accordance with the invention,

Fig 2 shows the component parts in Fig 1 in an assembled state in a section,

5 Fig 3 illustrates the locking device just before the insertion of a male connector pin,

Fig 4 illustrates a first locking state indicating a correct engagement,

10

Fig 5 illustrates a second locking state,

Fig 6 illustrates the opening of the locking device..

15

Detailed description of a preferred embodiment of the invention

20 In the description below, "longitudinal" relates to the longitudinal direction of the female connector part and "outer end" relates to the end of the locking device accessible from the outside. It should also be noted that all reference signs are not repeated throughout all drawings.

25

The component parts of a locking part 1 for a female connector according to a preferred embodiment are shown in an exploded view in Fig 1. The locking part comprises a hollow cylindrical part 5 with an end wall 8 in which a central opening 15 is located. The opening 15 is dimensioned to receive the contact pin of a standard male connector. The outside of the cylindrical part is provided with circumferential grooves 3 serving as space for excess glue when the cylindrical part is glued into a female connector part.

30

35

The locking device further comprises a locking washer 7 with a central opening 18. Two locking tongues 19, 19' are located on opposite sides of the opening 18 and extend into the opening. The distance between the tips is less than the diameter of the male connector pin to be locked into the locking device. The washer 7 has an outer shape that includes two parallel sides 17, 17'. The two parallel sides will bias the tongues towards the common plane of the washer. It should be noted that in this particular embodiment the sides have been designed to be parallel in order to define the bending force of the sides of the washer. The design may also be used for locking the washer against rotation, as will be described below in connection with an alternative embodiment.

The inside of the inner end wall is provided with a flange 9 around the opening 15. The flange has been placed in such a way that there will be a distance between the flange and the inner surface of the wall of the cylindrical part 5. The edge 11 of the flange facing the inside of the wall of the cylindrical part 5 is rounded. The flange 9 will serve as a pivot for the tongues.

The locking device further comprises a cylindrical plunger 4 fitting into the cylindrical part 5. The plunger is provided with a central bore 14 and the outside of the plunger is provided with a spiraling groove 6 intersecting a longitudinal groove 13. These grooves are intended to cooperate with an interior lug 12 located on the inside wall of the cylindrical part 5. The outer side of the outer end of the plunger 4 is provided with a peripheral groove 16 intended to sealingly hold an O-ring 20 against the inside of the cylindrical part 5. As seen in Fig 1a, a part 6' of the spiraling groove 6 passes beyond the intersection with the groove 13.

The inside of the inner end of the plunger 4 is provided with a conical surface 10, the wall of the plunger 4 thus tapering into a peripheral edge 21.

- 5 The outer end of the longitudinal bore of the plunger 4 is closed by means of a plug 2. The opening in the bore is enlarged by means of a slit permitting the insertion of a screwdriver or an equivalent tool.
- 10 In the assembled state, illustrated in Figs 2 - 6, the plunger 4 will keep the washer 7 in the vicinity of the flange 9. The plunger will be held in the cylindrical part 5 by means of the longitudinal slot 13, which permits a limited longitudinal movement.

15

The locking device is simple to assemble. The procedure only comprises the steps of:

- placing the washer 7 in the cylindrical part 5,
- 20 -mounting the sealing ring 20 in the groove 16 on the plunger 4,
- engaging the lug 12 in the slot 6 and turning the plunger until the lug 12 is located in the longitudinal slot 13.

- 25 The locking device 1 can be glued, welded or otherwise bonded into a tubular connector. The device of course also can be molded into a header.

- 30 A male connector pin 30 to be locked into the locking device 1 is inserted through the opening 15 in the end wall 8 as illustrated in Fig 3. As seen in Fig 4, the plunger 4 in this particular embodiment can move outwards together with the washer 7 when the pin 30 engages the washer 7. The outward movement is limited by the lug 12 engaging the inner
- 35 end of the slot 13. In the case in which the locking device is located in a through hole flush with the outer surface of the pacer in which it is to be mounted, the outward movement

will be an indication that the male connector pin 30 has been correctly inserted, see Fig 4.

Since the distance between the tips of the two tongues 19, 19' is less than the diameter of the pin 30, the tongues will be bent in the direction of insertion and consequently form an angle with the surface of the pin. The spring bias of the two parallel sides of the washer will urge the tongues into contact with the pin. The length and the stiffness of the tongues is such that the tongues in principle cannot swing past the plane of the washer. The pin therefore will be locked behind the end wall 8 against withdrawal from the connector.

When the pin has been fully inserted, the plunger 4 can be pushed back into the cylindrical part 5 so as to be flush with the outside of the housing as indicated in Fig 5.

If the pin is to be disconnected, the plunger 4 is pushed inwardly, the inner peripheral edge 21 engaging the peripheral ends of the washer 7 as illustrated in Fig 6. As a consequence, the tongues 19, 19' will swing around the flange and release the pin. The pin with lead then easily can be withdrawn.

The removal of the male pin 30 from the connector can be facilitated by removing the plug 2 from the plunger and screwing the plunger into the cylindrical part 5 by means of the groove 6'. The plunger 4 thus will deflect the tongues 19, 19' from the pin. The pitch of the groove is chosen such that the plunger 4 will remain in the rotational position of the screwed-in state in spite of the outward force exerted by the deformed washer 7. The pin then can be pushed out from the connector by means of a suitable tool that can be inserted through the opening of the bore 14.

It should be noted that, in the above embodiment, the washer is not locked against rotation. If however the washer is locked against rotation, it will be possible to locate the tongues (excluding the remaining parts of the washer) on a stud each instead on a circular flange. The studs also will serve as pivots for the tongues. In this case the force needed to swing the tongues out of engagements with the pin would be less, given that the dimensions of the washer remains the same (the spring bias of the tongues into engagement with the pin would however not be affected). In this embodiment the studs are located opposite each other adjacent the central opening 15. The inner side of the wall of the cylindrical part adjacent the studs is shaped to conform to the outer peripheral shape of the washer 7, thus also having two parallel sides in cross-section. The parallel sides are parallel to a center-line drawn through the two studs. In this way, the washer will be locked against rotation when the washer is located on the studs.

In this particular embodiment the inner part of the outside of the plunger would have to have a shape corresponding to the inner shape of the cylindrical part 5. Although the plunger still could be mounted in the cylindrical part by means of a spiraling groove, the option of opening the locking device by rotating the plunger discussed in connection with the above embodiment would be excluded. If this option also were desirable, the means for locking the washer against rotation would have to be located within the outer periphery of the washer and extend past the washer. The inside of the plunger would have to be hollowed to accommodate these means in order to allow the free rotation of the plunger to its innermost location.

The electrical connections from the female connector to the pulse generator are not a part of the present invention and thus are not shown in detail. The connections may for instance be made through circular springs 31 engaging the

contact surfaces 32 on the male connector 30, as for instance indicated in Fig 5. These rings are in turn connected to the interior of the pacer.

- 5 The cylindrical part 5 and the plunger 4 may be made of any suitable biocompatible material used in pacers, as for instance metals such as titanium, stainless steel, NP-35 alloy, or ceramics such as Al_2O_3 or of plastics such as macrolon, epoxy resin etc. The two parts may be made of the
- 10 same material or of different materials. The tongues and washer preferably is made of titanium, stainless steel or NP-35, but other biocompatible materials having a comparable resilience may of course be used.
- 15 The invention of course can be varied in many ways within the scope of the appended claims. In the above embodiments, the washer has been described as having two tongues. It is however quite possible to use only one tongue or more than two tongues. The tongues have been illustrated as being part
- 20 of a resilient washer, but they may of course be associated with separate springs for instance formed integrally with said tongues. The cylindrical part has been illustrated as a separate part, but may of course be an integral part of a pacer housing or header. In the widest sense, the plunger
- 25 may be any device transferring a pushing force for the exterior of the pacer to the peripheral parts of the washer.

- The male connector part has been illustrated above as being a standard IS-1 male connector with a complementary female
- 30 connector. The male connector part of course could be of any kind having an elongate shape, the female connector part having a corresponding complementary shape.

Claims

1. Locking device (1) for a female connector part for cooperation with an elongate, male connector part (30), said female connector part being intended for use in a pacer housing, said female connector part comprising a longitudinal bore defining a longitudinal space for said locking device, said locking device comprising one or several tongues (19, 19'), said tongues (19, 19') being swingable between two positions, a first position in which the tips of the tongues (19, 19') can engage said male elongate connector part (30) and a second position in which the tips of the tongues (19, 19') will not engage the male elongate connector part (30), said tongues being biased towards said first position by means of a spring force, **characterized** in that a pivot (9) is associated with each tongue, each tongue having a first part being located on one side of said pivot and engaging said connector means (30), a second part being located on the other side of said pivot, longitudinally acting means (4) being provided to act on said second part of said tongues for actuating said tongues (19, 19') from said first position against said bias to said second position.
2. Locking device according to claim 1, **characterized** in that said locking means (1) comprises a hollow cylindrical part (5) with an end wall (8) having a central opening (15).
3. Locking device according to claim 2, **characterized** in that said pivot (9) is located inside said opening (15) adjacent said opening (15).
4. Locking device according to claim 3, **characterized** in that said pivot is in the form of a flange surrounding said opening (15).

5. Locking device according to claim 3, **characterized** in that said pivots (9) are in the form of a stud for each tongue, said studs located adjacent said opening on the inner side of said wall (8).

5

6. Locking device according to anyone of the preceding claims, **characterized** in that said tongues (19, 19') are formed integrally with a washer (7) with a central opening (18), said tongues extending into said opening (18) so as to
10 define a distance that is smaller than the diameter of the male connector part to be locked in the locking device.

7. Locking device according to claim 6, **characterized** in that two tongues (19, 19') are provided, said tongues being
15 located opposite to each other.

8. Locking device according to claim 6, **characterized** in that three or more tongues (19, 19') are provided, said tongues being located symmetrically around the circumference
20 of said washer.

9. Locking device according to anyone of the preceding claims, **characterized** in that said longitudinally acting device is a plunger (4) with a central bore (14), said
25 plunger being slidable in said cylindrical part (5), said tongues (19, 19') being located between said end wall (8) and said plunger (4) and being seatable on said pivots.

10. Locking device according to claim 9, **characterized** in that said plunger is provided with a peripheral edge (21) acting on the peripheral part of said tongues.
30

Abstract

The invention relates to a locking device (1) for a female connector part for cooperation with an elongate, male connector part (30), said female connector part being intended for use in a pacemaker housing. Said female connector part comprises a longitudinal bore defining a longitudinal space for said locking device. Said locking device comprises one or several tongues (19, 19') being swingable between two positions, a first position in which the tips of the tongues (19, 19') can engage said male elongate connector part (30) and a second position in which the tips of the tongues (19, 19') will not engage the male elongate connector part (30). Said tongues are biased towards said first position by means of a spring force. A pivot (9) is associated with each tongue and each tongue has a first part engaging said connector means (30) and being located on one side of said pivot and a second part being located on the other side of said pivot. Longitudinally acting means (4) are provided to act on said second part of said tongues 19, 19') for actuating said tongues from said first position against said bias to said second position.

Fig 5.





FIG 2

2/3




FIG 3




FIG 4

3/3




FIG 5




FIG 6